



The manufacturer
may use the mark:



Valid until November 1, 2018
Revision 2.0 October 26, 2015



ANSI Accredited Program
PRODUCT CERTIFICATION
#1004

Certificate / Certificat Zertifikat / 合格証

ROT 1101097 C003

exida hereby confirms that the:

Rotex Solenoid & Air Operated Valves Type 32P

**Rotex Automation Limited
Vadodara, Gujarat - INDIA**

Have been assessed per the relevant requirements of:

IEC 61508 : 2010 Parts 1-7

and meets requirements providing a level of integrity to:

Systematic Capability: SC 3 (SIL 3 Capable)

Random Capability: Type A, Route 2_H Device

**PFD_{AVG} and Architecture Constraints
must be verified for each application**

Safety Function:

The Solenoid Valve will move to the designed safe position when De-energized / Energized within the specified safety time.

Application Restrictions:

The unit must be properly designed into a Safety Instrumented Function per the Safety Manual requirements.



Jack Gao

Evaluating Assessor

Sugay Sank

Certifying Assessor

Certificate / Certificat / Zertifikat / 合格証

ROT 1101097 C003

Systematic Capability: SC 3 (SIL 3 Capable)

Random Capability: Type A, Route 2_H Device

**PFD_{AVG} and Architecture Constraints
must be verified for each application**

Systematic Capability :

The product has met manufacturer design process requirements of Safety Integrity Level (SIL) 3. These are intended to achieve sufficient integrity against systematic errors of design by the manufacturer.

A Safety Instrumented Function (SIF) designed with this product must not be used at a SIL level higher than stated.

Random Capability:

The SIL limit imposed by the Architectural Constraints must be met for each element. This device meets *exida* criteria for Route 2_H.

32P Solenoid Valve Series Assessed¹

Valve Group	Valve Type Series	Description and Application
Type 32P-A	3008, 3008C, 3038, 3038C, 3055, 3055C, 3089C, 3166, 31119, 31120, 31123, 31147, 31205, 31209, 31210, 32301, 32347, I3003, I3004, I3005, I3008, M3002, M3008, M3009, M3010, M3011, M3017, P3001, P3003, P3006, P3007, P3008, P3009, & P3013	3/2 Single Solenoid Internal Pilot, De-energize To Trip (DTT) or Energize To Trip (ETT), ≤8 W Coils
Type 32P-B	51400, 51400C, 51424, 51424IS, 51424LW, 51424SEP, 51432, 51433, 51434, I5001, I5001EP, I5003, I5003EP, M5001, M5002, M5005, M5006, M5007, P5001, P5002, P5007 & P5009	5/2 Single Solenoid Internal Pilot, De-energize To Trip (DTT) or Energize To Trip (ETT), ≤8 W Coils
Type 32P-C	57400, 57404, 57405, I5002, I5002EP, I5004, I5004EP, P5004, P5005, & P5008	5/2 Double Solenoid Internal Pilot, Energize To Trip (ETT) only, ≤8 W Coils
Type 32P-D	33101 & 33347	3/2 Single Air Operated, De-energize To Trip (DTT) or Energize To Trip (ETT)
Type 32P-E	53400, & 53402	5/2 Single Air Operated, De-energize To Trip (DTT) or Energize To Trip (ETT)

IEC 61508 Failure Rates in FIT²

Valve Group and Application	λ_{SD}	λ_{SU}	λ_{DD}	λ_{DU}
32P-A Valve Types; DTT	0	222	0	213
32P-A Valve Types; ETT	0	46	0	333
32P-B Valve Types; DTT	0	263	0	378
32P-B Valve Types; ETT	0	74	0	503
32P-C Valve Types; ETT	0	91	0	539
32P-D Valve Types; DTT	0	152	0	135
32P-D Valve Types; ETT	0	44	0	236
32P-E Valve Types; DTT	0	220	0	362
32P-E Valve Types; ETT	0	88	0	478

¹ Excludes Latching Coil, ETT Manual Reset and Coils with Driver Circuitry (62 and 66) options

² FIT = 1 failure / 10⁹ hours

SIL Verification:

The Safety Integrity Level (SIL) of an entire Safety Instrumented Function (SIF) must be verified via a calculation of PFD_{avg} considering redundant architectures, proof test interval, proof test effectiveness, any automatic diagnostics, average repair time and the specific failure rates of all products included in the SIF. Each element must be checked to assure compliance with minimum hardware fault tolerance (HFT) requirements.

The following documents are a mandatory part of certification:

Assessment Report: ROT 11/01-097 R002 V2 R1 (or later)

Safety Manual: IM/V/060 Rev 2 (or later)

Rotex Solenoid &
Air Operated Valves –
Type 32P



64 N Main St
Sellersville, PA 18960

T-109, V1R1